

## Z3 2.8 roadster, Z3/2 2.8 Coupe

Reifendimension	Stahlscheiben- Rad (St.-Rad)	Leichtmetall- Rad (LM-Rad)	IS mm	Styling Nr.	
				St.	LM
<b>Sommer:</b> 225/50 ZR 16 <sup>2)</sup> 225/50 R 16 92W	-	7J x 16 7J x 16 7J x 16	45 46 47	-	17 10,16,18,25,26,30,32,35, 42,47 43,45,46
<b>17"-Mischbereifung: 1) 3)</b> VA: 225/45 ZR 17 HA: 245/40 ZR 17	- -	7½J x 17 (VA) 8½J x 17 (HA)	41 41	- -	18,32,38,42 18,32,38,42
<b>Winter (M+S):</b> 205/60 R 15 91Q/T/H	6½J x 15	7J x 15	47	1,12	6,10,13,14,17,18,27,28, 29,32,34,36,41
205/55 R 16 91Q/T/H 225/50 R 16 92Q/T/H	-	7J x 16 7J x 16 7J x 16	45 46 47	-	17 10,16,18,25,26,30,32,35, 42,47 43,45,46
225/45 R 17 91Q/T/H	-	7½J x 17 8J x 17	41 47	-	5,10,18,19,32,38,42 32,42,44,47,50,51
<b>Reserverad:</b> T 125/90 R 15 96M	3½B x 15	-	36	12	-

1) Keine Schneeketten zulässig.

2) Ausschließlich aufgeführte Reifenfabrikate zulässig

3) M-GmbH-Bereifung; M-Technik Fahrwerk empfohlen